



ELITE DAISY PANEL ACOUSTICS

LED

Suspended Lighting Fixtures With Lens

Luminaire suspendus Avec Lentille

APPLICATION AREAS

Shopping Malls
Supermarkets
Offices
Meeting rooms
Stores
Hospitals
Schools
Corridors

DOMAINES D'UTILISATION

Centres Commerciaux
Supermarchés
Bureaux
Salles de Réunions
Magasins
Hopitaux
Ecoles
Couloirs

BODY

Anodized aluminum with satin finishing. Black and white color options with elegant design.

LENS

With 50° or 80° lens.

DIFFUSER

UV stabilized frosted diffuser.

CONVERTER

Compatible with ENEC standards.

LED

LED modules with 60.000 hours lifetime LUMILEDS / SAMSUNG / NICHIA brand LEDs.

SUSPENSION

Composed of 1mm steel wire rope and nickel-plated brass components. Suspension height is adjustable. Supplied with transparent electric cord and ceiling mounted electrical junction box with aesthetic design.

CORPS

Corps en aluminium anodisé, satiné. Design élégant. Couleurs blanc, noir disponibles.

LENS

Avec lentille 50 ° ou 80 °.

DIFFUSEUR

Diffuseur givré. Anti UV.

CONVERTEUR

Convertisseur, conforme aux normes ENEC.

LED

Modules LED – Durée de vie 60.000 heures avec LED de marque LUMILEDS / SAMSUNG / NICHIA.

SYSTEME DE FIXATION

Composé d'un fil en acier de 1mm, de composants en laiton nickelés. Livré avec un cordon électrique transparent et une boîte de jonction électrique à fixer au plafond. Hauteur de fixation réglable.

NOTE

Lumen values are based on white body color measurements. Depending on different body colors lumen values may drop. For instance, there will be 9% drop for black body color.

V / Hz 220 - 240 / 50 - 60

Options

Dimmable electronic ballast or convertor.
Emergency kit

Options

Ballast électronique dimmable ou convertisseur.
Kit d'urgence.

NOTE

Given lumen values are net delivered luminaire output lumens.

Given power values are total consumed AC power of the luminaire.

NOTE

Les valeurs de lumens données sont les lumens de sortie nets du luminaire.

Les valeurs de puissance données sont la puissance AC totale consommée du luminaire.

Direct Lighting
Éclairage Direct





Color Options
Options de Couleur




Direct / LED Type / Type LED

Color Rendering Index / Indice de Rendu des Couleurs: (CRI): Ra>80

Code	Power Puissance (W)	LED Type Type De LED	LED Module Module LED	Lum. Flux Flux Lum. (lm)	Color Temperature Température De Couleur (K)	Dimensions (mm)			Weight Poids (kg)	Packing Quantity Colisage	Pcs./20" Container Pcs./20" Conteneur
						a	l	h			
PL10SA212L15L	32	2835 SMD	PCB	3870	2700 - 6500	47	578	73	1.2	2	3635
PL10SA213L15L	44	2835 SMD	PCB	5800	2700 - 6500	47	858	73	1.7	2	3635
PL10SA214L15L	58	2835 SMD	PCB	7730	2700 - 6500	47	1138	73	2.3	2	2835
PL10SA215L15L	74	2835 SMD	PCB	9660	2700 - 6500	47	1418	73	2.9	2	2295
PL10SA216L15L	88	2835 SMD	PCB	11600	2700 - 6500	47	1698	73	3.5	2	1970
PL10SA217L15L	104	2835 SMD	PCB	13530	2700 - 6500	47	1978	73	4.0	2	1560
PL10SA218L15L	120	2835 SMD	PCB	15460	2700 - 6500	47	2258	73	4.6	2	1560
PL10SA219L15L	132	2835 SMD	PCB	17390	2700 - 6500	47	2538	73	5.2	2	1560
PL10SA210L15L	150	2835 SMD	PCB	19320	2700 - 6500	47	2818	73	5.7	2	1255



80° Light Beam



50° Light Beam