

ELITE DAISY SIVA ALTI RECESSED ENCASTRE

LED

Sıva Altı Lensli Aydınlatma Armatürleri

Recessed Lighting Fixtures With Lens

Luminaires Encastrés Avec Lentille

UYGULAMA ALANLARI

Ofisler
Toplantı Odaları
Mağazalar
Hastaneler
Okullar
Koridorlar

APPLICATION AREAS

Offices
Meeting rooms
Stores
Hospitals
Schools
Corridors

DOMAINES D'UTILISATION

Bureaux
Salles de Réunion
Magasins
Hopitaux
Ecoles
Couloirs

GÖVDE

Elektrostatik toz boyalı sac.

LENS

50° veya 80° LEDİL lens.

KONVERTÖR

ENEC standartlarına uygun, uzun ömürlü sabit akımlı konvertör.

LED

60.000 saat ömürlü LUMILEDS / EDISON / NICHIA marka LED'li LED modüller.

BODY

Electrostatic powder coated sheetmetal.

LENS

50° or 80° LEDİL lens.

CONVERTER

Long life, low power loss converter with constant current. Compatible with ENEC standards.

LED

LED modules with 60.000 hours lifetime LUMILEDS / EDISON / NICHIA brand LEDs.

CORPS

Feuille de métal peinte électrostatiquement.

LENTILLE

LEDİL lentille 50° ou 80°.

CONVERTEUR

Convertisseur, conforme aux normes ENEC. Longue vie. Perte de puissance faible avec courant constant .

LED



Modules LED – Durée de vie 60.000 heures avec LED de marque LUMILEDS / EDISON / NICHIA.




LED'li Tip / LED Type / Type LED

Renk Geri Verim İndeksi / Color Rendering Index / Indice de Rendu des Couleurs: (CRI): Ra>80

Kod Code	Güç Power Puissance (W)	LED Tipi LED Type Type De LED	LED Modül LED Module Module LED	Işık Akısı Lum. Flux Flux Lum. (lm)	Renk Sıcaklığı Color Temperature Température De Couleur (K)	Ölçüler Dimensions (mm)					Ağırlık Weight Poids (kg)	Ambalaj Adedi Packing Quantity Colisage	Adet/20" Konteyner Pcs./20" Container Pcs./20" Conteneur
						a1	a2	b1	b2	h			
PL10A21E15C	2x6,8	2835 SMD	PCB	2170	2700 - 6500	295	275	595	575	23	2.5	4	1100
PL10A22E15C	4x6,8	2835 SMD	PCB	4340	2700 - 6500	295	275	1195	1175	23	2.5	2	575
PL10A41E15C	4x6,8	2835 SMD	PCB	4340	2700 - 6500	595	575	595	575	23	2.5	2	570



80° Işık Açısı / 80° Light Beam



50° Işık Açısı / 50° Light Beam

V / Hz 220 - 240 / 50 - 60

Opsiyonlar	Options	Options
DIM edilebilir elektronik balast yada konvertör. LED'li modeller için acil durum kiti.	Dimmable electronic ballast or convertor. Emergency kit for models with LED	Ballast électronique dimmable ou converteur. Kit d'urgence pour les modèles LED.
NOT	NOTE	NOTE
Belirtilen lümen değerleri LED üzerindeki lümen değerleridir. Belirtilen güç değerleri LED üzerindeki DC güç değerleridir.	Given lumen values are values on LED. Given power values are DC power values on LED.	Les valeurs de lumen données sont les valeurs sur LED. Les valeurs de puissance données sont les valeurs de courant continu puissance sur LED.